

STAND WITH HYDR. ADJUSTMENT FOR HYPODERMOCLYSIS PNT 703 R



Stand with hydraulic height adjustment for hypodermoclysis, for washing and surgical irrigation. Hydraulic pump with pedal for height adjustment. Stainless steel AISI 304 tubular structure. 4 stainless steel AISI 304 hooks, with anti-release safety device. Mounted on a 5 spoke stainless steel base with 5 castors diam. 75 mm. (2 antistatic with brake, 3 standard) and grey vipla bumpers. Stainless steel adjustable gripping handle for easy transport.

Price without transport and taxes:

950,00 €

Contact us for a quotation!

Technical Data:

Structure:

Rod: hydraulic pump with stainless steel sleeve

Base: in stainless steel AISI 304 chrome nickel 18/10 - UNI X5 CrNi1810; thickness 5 mm.

Finish:

Rod: polished stainless steel

Base: brushed stainless steel

Other components:

Such as screws and other mechanical parts, different materials suitable for the purpose are used.

Cleaning:

Normal detergents can be used for cleaning, provided they do not contain chlorine and its compounds. When cleaning, it is important to follow the satin finish of stainless steel, without exerting too much pressure. For extremely stubborn stains, specific products for stainless steel should be used.

Important notes:

1. Do not use scouring pads or anything else that may scratch or scrape.
2. Avoid using muratic or bleach,
3. Do not leave iron for a long time.

Dimensional Data	
Dimensions (L x W x H) Cm	147 / 247
Capacity max. Kg	28
Net weight Kg	20,5
Gross weight Kg	22,0
Volume in cube Mt.	0,06
Number of items	2
Packing (L x W x H) Cm (Base)	60 x 14 x 62
Packing (L x W x H) Cm (Rod)	10 x 10 x 150